

FIG.1




FIG.2




FIG.3




FIG.4




IMAGE-PIC ELEMEN OPERATI	
<b>IG.5A</b>	
Ĭ	

-PICKUP MENT RATION


FIG.5B SHAPE-VARIABLE MIRROR DRIVEN

**DRAFT MODE** HELD FRAME READOUT MODE OPENED EXPOSURE OPERATION HELD **DRAFT MODE** 

Appln. No. 10/705,239 Date Filed: November 12, 2003 Reply to Missing Parts dated February 25, 2004

Replacement Sheet

FIG.6




	<del></del>	
DRAFT MODE OPEN HELD	FRAME READOUT MODE	E FRAME READOUT MODE CLOSE
	EXPOSURE	EXPOSURE
FRAME READOUT MODE CLOSE OPENED	FRAME READOUT MODE	FRAME READOUT MODE CLOSE
EXPOSURE	EXPOSURE	EXPOSURE
DRAFT MODE OPEN HELD	DRAFT MODE	DRAFT MODE E E OPEN
IMAGE-PICKUP ELEMENT OPERATION MECHANICAL SHUTTER SHAPE-VARIABLE MIRROR DRIVEN	IMAGE-PICKUP ELEMENT OPERATION SHAPE-VARIABLE MIRROR DRIVEN	IMAGE-PICKUP ELEMENT OPERATION MECHANICAL SHUTTER SHAPE-VARIABLE MIRROR DRIVEN
FIG.7A FIG.7B FIG.7C	FIG.8A FIG.8B	FIG.9A FIG.9B FIG.9C
<del></del>	<del></del>	

Appln. No. 10/705,239 Date Filed: November 12, 2003 Reply to Missing Parts dated February 25, 2004


Replacement Sheet

## **FIG.10**



Appln. No. 10/705,239 Date Filed: November 12, 2003

Reply to Missing Parts dated February 25, 2004 Replacement Sheet




Appln. No. 10/705,239
Date Filed: November 12, 2003

Reply to Missing Parts dated February 25, 2004

Replacement Sheet

## **FIG.12**



**FIG.13** 

INPUT	ОИТРИТ				
	V1	V2	V3	V4	V5
0	D0_1	D0_2	D0_3	D0_4	D0_5
1	D1_1	D1_2	D1_3	D1_4	D1_5
2	D2_1	D2_2	D2_3	D2_4	D2_5
3	D3_1	D3_2	D3_3	D3_4	D3_5
•		•	•	•	•
•	•	•	•	•	•
•	•	•	•	•	•
125	D125_1	D125_2	D125_3	D125_4	D125_5
126	D126_1	D126_2	D126_3	D126_4	D126_5
127	D127_1	D127_2	D127_3	D127_4	D127_5

**FIG.14** 

FOCAL DISTANCE	LUT INPUT		
CONVERTED TO 35 mm FILM (mm)	MINIMUM PICTURING DISTANCE	INFINITY	
35	10	98	
50	20	108	
. 65	30	118	
80	24	112	
95	18	106	